

SAFETY DATA SHEET

SUMNER GRIP

29 August 2012



Section 1: IDENTIFICATION OF SUBSTANCE AND SUPPLIER

Product name: SUMNER GRIP
Other names: SUMNER GRIP
CAS number: Unassigned
Recommended uses: High strength adhesive for Masonry Veneers
Company Details: **SUMNER Schist**
Address: 177 Marua Road, Ellerslie
Telephone Number: 021 657 659
Hours: 9am – 5pm

Emergency Telephone Number:

(0800) 764-766 24 hours.

National Poisons Centre,
Department of Preventative and Social Medicine,
University of Otago,
P O Box 913,
Dunedin,
New Zealand.

Date of Revision: 29 August 2012

Date of next review: 29 August 2017

Section 2: HAZARDS IDENTIFICATION

Hazard Classification: Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001

HSNO Approval Number: Classified under the group standard:
Construction Products (toxic [6.7A]) Group Standard 2006

HSNO Approval Number: HSR002545

Hazard classification: 6.1 E Acutely toxic
6.3A Skin irritant
6.5A Respiratory sensitiser
6.5B Contact sensitiser
6.7A Carcinogenic
6.9B Target organ toxicant
8.3A Eye corrosive

DANGER : May cause allergy or asthma symptoms or breathing difficulties if inhaled
May cause cancer

SAFETY DATA SHEET

SUMNER GRIP

29 August 2012

Causes serious eye damage

WARNING: If medical advice is needed have product container or label at hand
Keep out of reach of children
May be harmful if inhaled and cause respiratory irritation
Causes skin irritation including allergic skin irritations

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Ingredient	Concentration
Sand	45 – 60 %
Cement	30 – 45 %
Redisperable polymer	3 - 7%

Sand

Ingredients	CAS number	Content (%w/w)
Silica – crystalline (quartz)	14808-60-7	<50%
Naturally occurring metal oxides	Not known	<5%
Innocuous silicates	Not known	Balance

Cement

Ingredient	CAS numbers	Concentration % by weight
Tri calcium silicate	12168 – 85 - 3	42 – 70
Di calcium silicate	1003 – 77- 2	15 – 30
Tri calcium aluminate	12042 – 78- 3	1 – 13
Tetra calcium alumino ferrite	12068 – 35 – 8	1 – 15
Magnesium oxide	1309 – 48 – 4	0.1 – 2.0
Calcium oxide	1305 – 78 – 8	0 – 3
Sodium salts		0.1 – 0.7
Potassium salts		0.1 – 1.0
Gypsum	13397 – 24 – 5	4 – 7
Ground granulated blast furnace slag		0 - 65

Redispersible polymer

Copolymer of vinyl acetate and ethylene with mineral additives and protective colloid. Non-hazardous.

Section 4: FIRST AID MEASURES

Swallowed: Rinse mouth. No NOT induce vomiting.
Call the doctor / physician or poison centre

Eye contact: Rinse cautiously with water for several minutes.
Remove contact lenses if present and easy to do so.
Continue rinsing for at least 15 minutes.
Keep patient calm.
Immediately call the doctor or poison centre

SAFETY DATA SHEET

SUMNER GRIP

29 August 2012

Skin:	Remove contaminated clothing and wash skin with plenty of soap and water. Seek medical attention if irritation or rash develops. If concerned, seek medical advice. Launder contaminated clothing before reuse
Inhaled:	Remove to fresh air. Do not induce vomiting If breathing is difficult keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms, or feeling unwell, call the poison centre or doctor
Required instructions:	For advice contact the National Poisons Centre 0800 POISON (0800 764 766) or contact a doctor
Workplace facilities:	Eye wash and safety shower facilities are recommended

Section 5: FIRE FIGHTING MEASURES

Type of hazard:	Not classed as flammable
Fire hazard properties:	Non flammable. No fire or explosion hazard exists
Regulatory requirements:	Not applicable
Extinguishing media and methods:	Not applicable
Hazchem code for fire:	Not applicable
Recommended protective clothing:	Not applicable

Section 6: ACCIDENTAL RELEASE MEASURES

Emergency procedures:	If spilt (bulk) contact emergency services if applicable. Wear dust proof goggles, PVC / rubber gloves, a Class P1 (Particulate) respirator (where an inhalation risk exists), coveralls and rubber boots. Prevent spill from entering drains or waterways. Collect and place in sealable containers for disposal. Avoid generating dust
------------------------------	--

Section 7: HANDLING AND STORAGE

Precautions for safe handling:	Read label and safety data sheet before use. Obtain special instructions. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wear protective gloves, eye and face protection. Use only in a well ventilated area.
Regulatory requirements:	Approved handlers and tracking not required. Corrosive signage where quantities greater than 1 000kg are present. Emergency response plans for toxic response are

SAFETY DATA SHEET

SUMNER GRIP

29 August 2012

required where quantities greater than 1 000kg are present. Corrosive emergency response plans are required when holding more than 10 000kg.

Handling practices:

Avoid contact with eyes and wear eye protection.
Keep containers adequately sealed during material transfer, transport, or when not in use.
Use safe work practices to avoid eye or skin contact and inhalation.
Observe good personal hygiene, including washing hands before eating.
Prohibit eating, drinking and smoking in contaminated areas (e.g. if container is damaged).
Wash exposed skin thoroughly after handling

Conditions for safe storage:

Ensure packages are adequately labelled, protected from physical damage and sealed when not in use.

Store site requirements:

Store in a cool, dry, well-ventilated areas, away from moisture, oxidising agents (e.g. hydrogen fluoride, phosphorus oxide), acids, ethanol, interhalogens (e.g. chlorine trifluoride) and foodstuffs

Packaging:

Ensure packages are labelled, protected from physical damage and sealed when not in use.

Section 8: EXPOSURE CONTROL / PERSONAL PROTECTION

Workplace exposure standards:

Lime (1305-78-8) TWA 2 mg/m³
Silica, crystalline – quartz (14808-60-7) TWA 10 mg/m³
Aluminium oxide (1344-28-1) TWA 10 mg/m³ (note: the value is for inspirable dust containing no asbestos and less than 1% free silica)
Ferric oxide (1309-37-1) TWA 5 mg/m³
Sodium oxide (1313-59-3) data not available
Hexavalent chromium (Cr(VI)) (18540-29-9) TWA 0.05 mg/m³

Application in the workplace:

Use with adequate natural ventilation. Where dust inhalation hazard exists, mechanical extraction ventilation is recommended

Exposure standards outside the workplace:

No TEEL or EEL is set for this substance at this time

Engineering controls:

Where possible ventilation should be used (with suitable dust trap or filter) to maintain the environment below the workplace exposure standard

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Loose material consisting of sand and cement

SAFETY DATA SHEET

SUMNER GRIP

29 August 2012

pH: 11 – 13
Melting point: > 1 200 °C
Vapour pressure: Not known
Solubility: < 10g/L

Section 10: STABILITY AND REACTIVITY

Stability of the product: Stable
Conditions to avoid: Water contact may increase the product temperature 2-3 °C
Material to avoid: Wet cement dust is alkaline. It is incompatible with oxidizing agents (e.g. hypochlorites), ethanol, acids (e.g. hydrofluoric acid) and interhalogens (e.g. chlorine trifluoride)

Hazardous decomposition products:
May evolve toxic gases if heated to decomposition

Section 11: TOXICOLOGICAL INFORMATION

Summary

Corrosive.
Avoid eye and skin contact or dust inhalation.
This product has the potential to cause acute and chronic health effects with prolonged exposure
This product contains crystalline silica.
Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious harm disease which can lead to fatal lung disease.

Eye Corrosive.
Severe irritant upon contact with powder / dust.
Over exposure may result in pain, redness, corneal burns and ulceration with possible permanent damage

Inhalation Corrosive.
Over exposure may result in severe mucous membrane irritation and bronchitis.
Hexavalent chromium is reported to cause respiratory sensitization, however due to the trace amounts present a hazard is not anticipated under normal conditions of use.

Ingestion Corrosive.
Ingestion may result in burns to the mouth and throat, with vomiting and abdominal pain. Due to product form, ingestion is not considered a likely exposure route

Skin Corrosive. Prolonged and repeated contact with powder or wetted form may result in skin rash, dermatitis sensitisation.

TEL No TEL is set for this substance at this time.

Section 12: ENVIRONMENTAL INFORMATION

Aquatic Not classified as an aquatic ecotoxic under the Hazardous Substances and New Organisms Act

SAFETY DATA SHEET

SUMNER GRIP

29 August 2012

Soil Not classified as an soil ecotoxic under the Hazardous Substances and New Organisms Act

Terrestrial vertebrates Not classified as toxic to terrestrial vertebrates under the Hazardous Substances and New Organisms Act

Terrestrial invertebrates Not classified as toxic to terrestrial invertebrates under the Hazardous Substances and New Organisms Act

EEL No EEL is set for this substance at this time

Section 13: DISPOSAL CONSIDERATIONS

Disposal information Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil to prevent dust generation and dispose of to an approved landfill site

Section 14: TRANSPORT INFORMATION

Relevant information: None

Other requirements : Not regulated for transport purposes

Section 15: REGULATORY INFORMATION

Regulatory status: ERMA Approval code : HSR002545 - Group standard For Construction Products (toxic [6.7A]) Group Standard 2006. For full listing of controls see www.ermanz.govt.nz

Section 16: OTHER INFORMATION

Relevant information mg/m³ – milligrams per cubic metre
ppm – parts per million
TWA – time weighted average
pH – relates to hydrogen ion concentration – this value relates to a scale of 0 – 14 where 0 is highly acidic and 14 is highly alkaline

Additional information None

Although reasonable care has been taken in the preparation of this document, Stone On Line extends no warranties and makes no representations as to the accuracy or completeness of the information contained therein, and assumes no responsibility regarding the suitability for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose (s).